

Intrinsically Safe Hammer Union Pressure Transmitter



The Hammer Union Pressure Transmitter is designed for the rugged environments of land based and offshore drilling installations including Mud Logging and Measurement while drilling.

Features

- Ranges to 20,000 psi
- 4-20 mA or 0-5 VDC output
- 1502 or 2002 / 2202 fitting
- Exceptional shock and vibration resistance
- $\pm 0.25\%$ accuracy of full scale
- CSA/ATEX/IECEX Approved

Datos fiscales:


Corporación Eco Industrial y Comercial S.A de C.V.
Plan de San Luis # 101 Int. 801 Col. El Coecillo
León, Gto. C.P. 37260

Oficina de Ventas:

Cd. de México
Cd. de Querétaro
Nextel

Tel (55) 5510-4265
Tel (442) 212-8075
Tel 01 (442) 413 7630
Tel 01 (442) 410 1565

Hammer Union Specifications



Performance

- Accuracy (linearity, hysteresis, & repeatability): $\pm 0.25\%$ of full scale (BFSL)
- Standard Pressure Ranges: 0-20,000 psis
- Overpressure - 1.5 times full scale (applies to sensor only, not fitting)
- Burst Pressure - 3 times full scale (applies to sensor only, not fitting)
- Compensated Temp: -40 - 65°C (-40 - 150°F)
- Temp Effects on Zero & Span: $\pm 0.026\%$ FSO/°C ($\pm 0.01\%$ FSO/°F)
- Life: 10 million cycles minimum
- Frequency Response: Less than 5ms

Environmental

- Storage Temp: -50 - 120°C (-50 - 248°F)
- Operating Temp: -40 - 85°C (-40 - 185°F)
- Enclosure Protection: IP67

Certification

- CSA/cCSAus Contract #237484
- IS: Class 1, Division 1; Groups C & D
Class 1, Zone 0, AEx ia IIB T4
Ex ia IIB T4
Ambient: -40 - 85°C
- ATEX: 4-20 mA
CE 0344 EX II 1G Ex ia IIB T4 Ga
(Ta = -40°C to +85°C)
- IECEx: 4-20 mA
EX ia IIB T4 Ga (Ta = -40°C to +85°C)

Connectivity

- Output Signal @ 21°C:
4-20 mA: 3-30 mA max
0-5 VDC: 110 mA inrush current
0-5 VDC: 3.5 mA operating current

Electrical

- Supply Voltage: 10-28 VDC on sensor
- Loop Resistance: 1012 ohms @ 28 VDC decreasing linearly to 0 ohms @ 10 VDC
- Insulation Resistance: >100 megaohms @ 500 VAC, 70°C
- Shunt Cal: 100% of full scale output



Physical

- Wetted Materials: Conforms to NACE MR-01-75 and ISO 15156-3 standards
- Incoloy

Datos fiscales:

Corporación Eco Industrial y Comercial S.A de C.V.
Plan de San Luis # 101 Int. 801 Col. El Coecillo
León, Gto. C.P. 37260

Oficina de Ventas:

Cd. de México
Cd. de Querétaro
Nextel

Tel (55) 5510-4265
Tel (442) 212-8075
Tel 01 (442) 413 7630
Tel 01 (442) 410 1565

Options

Part Number: HU - - IS - - PSIS - - -
 A B C D E

A. Output

- L24** 4-20 mA with Cal Shunt
- L27** 0-5 VDC

B. Pressure Range

- 5K** 0 - 5,000 psis
- 6K** 0 - 6,000 psis
- 10K** 0 - 10,000 psis
- 15K** 0 - 15,000 psis
- 20K** 0 - 20,000 psis (2002 fitting only)

C. Electrical Connection

- E1** 4 pin 'Mini'
- E2** 5 pin 'Mini'
- E3** 4 pin Threaded MS3102 (0-5V)
- E4** 6 pin Bayonet (0-5V)
- E5** 1/2 NPT coupling flying leads
- E6** 3 pin Turck Minifast (RSFVL36)
- E9** 3 pin Threaded MS3102 (4-20 mA loop)
- E10** Junction Box (1502 only)
- E12** 3 pin Bayonet (4-20 mA loop)
- E13** 7 pin Jupiter (4-20 mA loop w/Shunt Cal)
- E18** 4 pin Rota (4-20 mA loop w/Shunt Cal)
- E20** 4 pin Turck minifast (P-RSFV 40-0.3)

D. Fitting

- P34** Large Hammer Union 1502 Weco fitting
- P35** Small Hammer Union 2002 / 2202 Weco fitting
- P36** Large Welded Hammer Union 1502 Weco fitting
- P37** Small Welded Hammer Union 2002 / 2202 Weco fitting

E. Enclosure

- K0** No options (standard)
- K7** With handle*
- K1** With protective cage assembly*

*Consult factory



Datos fiscales:

Corporación Eco Industrial y Comercial S.A de C.V.
Plan de San Luis # 101 Int. 801 Col. El Coecillo
León, Gto. C.P. 37260

Oficina de Ventas:

Cd. de México
Cd. de Querétaro
Nextel

Tel (55) 5510-4265
Tel (442) 212-8075
Tel 01 (442) 413 7630
Tel 01 (442) 410 1565


Hammer Union Pressure Transducer Built for the Toughest Applications



Automation Products Group, Inc. brings you the highest quality hammer union pressure transducer on the market.

There's a reason why so many are switching to the APG hammer union pressure transducer. We always use a NACE compliant nickel alloy and welded construction for the toughest applications in Oil & Gas drilling and production.

Next time you need a hammer union pressure transducer, call us at (888) 525-7300.



Datos fiscales:

Corporación Eco Industrial y Comercial S.A de C.V.
Plan de San Luis # 101 Int. 801 Col. El Coecillo
León, Gto. C.P. 37260

Oficina de Ventas:

Cd. de México
Cd. de Querétaro
Nextel

Tel (55) 5510-4265
Tel (442) 212-8075
Tel 01 (442) 413 7630
Tel 01 (442) 410 1565