

IRU-3430 Ultrasonic Level Sensor




The IRU-3430 series provides a non-contact method of detecting level, presence/absence detection, volume, proximity and distance. With built in technology to compensate for unpredictable variables such as humidity, temperature and agitators the IRU-3430 is the right sensor for your application.

Features

- AutoSense Software for hassle-free setup
- Internal Temperature Compensation
- Works on solids and liquids

IRU-3430 Specifications



Performance

- Operating Range: 1.25 - 50 ft. (0.4 - 15.2 m)
- Beam Pattern: 9° off axis
- Internal Temperature Compensation
- Frequency: 43 kHz
- Accuracy: $\pm 0.25\%$ of detected range
- Resolution: 0.1 in. (2.5 mm)
- Response Time: Programmable (20 ms minimum)

Connectivity

- Output:
- 4-20 mA
 - 4-20 mA with (2) NPN outputs

Environmental

- Ratings: IP65
- Operating Temp: -40° - 140°F (-40° - 60°C)

Certification

- Class 1, Div. 2, Groups A, B, C, D
- IP65

Electrical

- Total Current Draw: 75 mA @ 24 VDC
- Supply Voltage: 12-28 VDC
- Wiring Connection: 4 or 5 conductor shielded cable

Programming

- Interface with RST-3001 Programmer (purchase separately - powered by USB)
 - The RST-3001 is 32 bit only
 - The RST-3002 is 32 and 64 bit compatible
- User selected units of measure

Physical

- PC/PET upper housing
- PC/PET Blend Transducer

Common Model Configurations

Model Number	Model Description
IRU-3433-C6	1.25 - 50 ft range, 43 kHz, 3" MNPT, 4-20 mA Output, 6 ft cable
IRU-3433-M	1.25 - 50 ft range, 43 kHz, 3" MNPT, 4-20 mA Output, Microconnector
IRU-3435-C6	1.25 - 50 ft range, 43 kHz, 3" MNPT, 4-20 mA / 2 NPN Outputs, 6 ft cable
IRU-3435-M	1.25 - 50 ft range, 43 kHz, 3" MNPT, 4-20 mA / 2 NPN Outputs, Microconnector

IRU-3430 Accessories

Please order separately, by part number.

Description	Part Number
Over Molded Extension Cables with Foil Shield	
4 Conductor	
Straight, 2 m	135407-0002
Right Angle, 2 m	135407-1002
Straight, 5 m	135407-0005
Right Angle, 5 m	135407-1005
5 Conductor	
Straight, 2 m	135415-0002
Right Angle, 2 m	135415-1002
Straight, 5 m	135415-0005
Right Angle, 5 m	135415-1005
Programming Module	
RST-3001 (USB - 32 bit only)	125389
RST-3002 (USB - 32 and 64 bit compatible)	125389-1000

Model Configuration Options

Model Number: IRU - 343 _____ - _____
AB

A. Output

- ☐ 34-20 mA
- ☐ 54-20 mA with (2) NPN outputs


B. Cable/Microconector

- ☐ CL Cable (Specify L=length in feet)
Standard 6 feet of cable
- ☐ MMicro Connector

Wiring

IRU-3433-C	
Red	+24 VDC
Black	Ground
White	mA+

IRU-3433-M	
1 Brown	+24 VDC
2 White	Not used
3 Blue	Ground
4 Black	mA+
5 Grey	Not used



IRU-3435-C			
Red	+24 VDC	Orange	mA+
Black	Ground	Green	NPN2
White	NPN1		

IRU-3435-M	
1 Brown	+24 VDC
2 White	NPN 1
3 Blue	Ground
4 Black	mA+
5 Grey	NPN 2

